


ED400FD_230V * // metal lathe



highlights

- serially equipped with leadscrew for thread cutting and automatic longitudinal feed
- induction-hardened and precision ground prismatic bed way guides
- hardened main spindle bedded with adjustable taper roll bearings
- high spindle centricity assures maximal turning accuracy
- spindle speed steplessly adjustable, speed can be read off conveniently from digital speed display
- comes with change gears delivering an exceptionally broad thread cutting range
- guides conveniently adjustable via V-ledges ensuring precision for many years
- powerful, maintenance free motor with undervoltage release
- smooth power transmission delivers constant torque
- tailstock can be adjusted for taper turning
- CW/CCW run mode
- Note: Machine runs at half speed when reversing.

included in delivery: 3-jaw chuck Ø 100mm, 4-way tool post, dead center MT3, dead center MT2, chuck guard, chip tray, change gears, tools



1.099,00

ED400FD_230V * // metal lathe



technical details

motor power s1 in W	450	voltage	230V / 50Hz
motor power s6 in W	630	cable length	1,7 m
bed width in mm	100	total dimensions in mm	940 x 380 x 345
range of metric threads in mm/r	0,5-3 (14)	lathe spindle speed in min-1	50-2500
max. swing over cross slide in mm	134	range of inch threads	8-44 (10)
tailstock cone	MK2/MT2	spindle nose mount	MK3/MT3
spindle bore in mm	21	carriage travel in mm	376
tailstock sleeve travel	55	cross slide travel in mm	80
compound slide travel in mm	55	distance between centers in mm	400
max. swing over bed in mm	210	longitudinal feed	0,089 / 0,147 / 0,198 mm/ U
max. tool holder cross-section	10 mm	gross weight in kg	75
net weight in kg	68	packaging length in mm	900
packaging width in mm	450	packaging height in mm	460
EAN code	9120039901329		